

# SHENZHEN ACONLED TECHNOLOGY CO., LTD.

www.aconled.com / Whatsapp: +86 18682069952

Contact: Danny / Email: Danny@aconled.com

## Rental LED Display Specification

Item	P2.9	P3.9	P4.8
Pixel Pitch	2.976mm	3.906mm	4.807mm
LED Type	SMD1415	SMD1921	SMD1921
Module Resolution	84dots x 84dots	64dots x 64dots	52dots x 52dots
Driving Mode	1/21scan	1/16scan	1/13scan
Module Pixels	7,056dots	4,096dots	2,704dots
Module Size	250mm x 250mm	250mm x 250mm	250mm x 250mm
Cabinet Size	500mm x 500mm	"500mm x 500mm or 500mm x 1,000mm"	"500mm x 500mm or 500mm x 1,000mm"
Cabinet Resolution	168dots x 168dots	"128dots x 128dots or 128dots x 256dots"	"104dots x 104dots or 104dots x 208dots"
Pixel Density	112,896dot/m <sup>2</sup>	65,536dots/m <sup>2</sup>	43,264dots/m <sup>2</sup>
Minimum Viewing Distance	≥2.9m	≥3.9m	≥4.8m
Brightness	≥4,000nits	≥4,500nits	≥4,500nits
IP Grade	IP65	IP65	IP65
Refresh Rate	1,920Hz~3840Hz	1,920Hz~3840Hz	1,920Hz~3840Hz
Gray Scale	13bits~18bits	13bits~18bits	13bits~18bits
Viewing Angle	H:160°/V:160°	H:160°/V:160°	H:160°/V:160°
Maximum Power Consumption	550W/m <sup>2</sup>	550W/m <sup>2</sup>	550W/m <sup>2</sup>
Average Power Consumption	185W/m <sup>2</sup>	185W/m <sup>2</sup>	185W/m <sup>2</sup>
Cabinet Weight	7kg/panel	7kg/panel or 14kg/panel	7kg/panel or 14kg/panel
Cabinet Material	Die-casting Aluminum	Die-casting Aluminum	Die-casting Aluminum
Operating Temperature	- 20°C~65°C	- 20°C~65°C	- 20°C~65°C